

1610 **WX1 METALIZED WAX**



DESCRIPTION Self-polishing metallized floor polish with high cross-linked polymers – for high traffic

SPECIFICATIONS High-shine self-polishing emulsion suitable for all floors

The protective film is highly resistant to traffic and has an anti-slip and dirt repellent effect Easy to apply and requires a short drying time Leaves a pleasant fragrance in the environment

HOW TO USE AND DOSING Only treat carefully dewaxed, rinsed and dried floors. Apply product to floor and spread evenly with a mop or wax applicator. Leave to dry completely for at least 30 minutes. Apply a second coat of wax making sure you work across the first coat to achieve

SPECIFICATION Appearance: Transparent white liquid

Specific weight [g/ml]: 1.030 +/- 0.020

The data given above are typical manufacturing values and not a specification.

PRODUCT COMPATIBILITY If in doubt, test material compatibility on a small concealed part before use.

USE & STORAGE The product is formulated for professional use only. Store in original containers. Avoid extreme temperatures. Consult safety sheet for further information on use and disposal. **PRECAUTIONS**

CERTIFICATIONS/ The surfactants contained in this product are biodegradable according to the criteria defined by Regulation (EC) 648/2004 and subsequent amendments. CONFORMITY

CHEMICAL COMPOSITION Consult safety sheet for further information on product ingredients.











Discover further informations on your smartphone.







